

# ePower DC UPS



- Built-in Li-ion battery
- Microprocessor controller guarantees high reliability
- Auto start when plugged in
- Manual power off switch
- Multi-color indicator
- Overload, short-circuit, over-charge and over-discharge protection



Backup Time Table : (For Reference)	
12V/1A Router	150 mins
12V/1.5A Router	120 mins
12V/2.0A Router	90 mins

## ePower DC UPS Specification

MODEL		ePower
<b>AC INPUT</b>		
Voltage Range	90 VAC ~ 264 VAC	
Frequency	50 or 60 Hz	
Surge protection	1.5KV (Optional K.21 enhanced, 6KV)	
<b>DC OUTPUT</b>		
Voltage	12VDC ± 5%	
Max. Power	25W (2.1A)	
<b>BATTERY</b>		
Type	Lithium-ion Battery	
Voltage	3.7VDC	
Capacity	2600mAh	
Typical Charging Time	3 hours recover to 90% capacity	
<b>PROTECTION</b>		
Battery	Deep Discharge, Over-charge and Short Circuit Protection	
Input/Output	Fuse for Short Circuit and Overload Protection	
<b>INDICATORS</b>		
LED	Full Battery	Green lighting
	Battery Charging	Constant flashing on Green LED
	Battery Discharging	Quick flashing on Green LED
	Fault	Red lighting
<b>PHYSICAL</b>		
Input Plug	Mounted on the housing (NEMA/UK/Schuko)	
Output Cable	1m Length (DC Male Jack, OD 4mm, ID 1.7mm or OD 5.5mm, ID 2.5mm)	
Dimension, D x W x H (mm)	68 x 42 x 74	
Net Weight (g)	280	

Product specifications are subject to change without further notice.