

# Alps



- Compatible to 19" cabinet
- Sine wave output
- Excellent microprocessor control guarantees high reliability
- Built-in AVR for voltage stabilization
- Auto restart while AC is recovering
- Off-mode charging
- Cold start function

## Alps Rack-Mount Line Interactive UPS Selection Guide

MODEL	ALPS500	ALPS750	ALPS1200	ALPS2200	ALPS3000
<b>CAPACITY</b>	500 VA / 300 W	750 VA / 450 W	1200 VA / 720 W	2200 VA / 1320 W	3000 VA / 1800 W
<b>INPUT</b>					
Voltage	230 VAC $\pm$ 10%				
Voltage Range	170 - 280 VAC				
Frequency Range	50 Hz / 60 Hz $\pm$ 5Hz				
Input Protection	5A/250Vac (AC Fuse)	5A/250Vac (AC Fuse)	10A/250Vac (AC Breaker)	15A/250Vac (AC Breaker)	20A/250Vac (AC Breaker)
<b>OUTPUT</b>					
Voltage	230 VAC				
AC Voltage Regulation (Batt. Mode)	$\pm$ 10%				
Frequency Range (Batt. Mode)	50 Hz / 60 Hz $\pm$ 1Hz				
Transfer Time	Typical 4ms, 10ms max				
Waveform (Batt. Mode)	Sinewave				
<b>BATTERY</b>					
Battery Type & Number	6V / 9Ah x 2	6V / 10Ah x 2	12V / 7Ah x 2	12V / 10Ah x 2	12V / 10Ah x 3
Typical Recharge Time	8 hours recover to 90% capacity				
<b>INDICATORS</b>					
LCD Display	AC Mode, Battery Mode, Load Level, Battery Level, Input Voltage, Output Voltage, Overload, Fault, and Low Battery				
<b>PROTECTION</b>					
Full Protection	Overload, discharge, and overcharge protection				
<b>PHYSICAL</b>					
Dimension, D x W x H (mm)	280 x 438 x 44		310 x 438 x 88		400 x 438 x 88
Net Weight (kgs)	7.6	8.1	11.1	14.9	20.7
<b>ENVIRONMENT</b>					
Humidity	0 to 90% RH @ 0 - 40°C (Non-condensing)				
Altitude	0-2000m				
Noise Level	Less than 40dB			Less than 45dB	

Product specifications are subject to change without further notice.